

Technical Specifications

APC Easy UPS Online 2000VA, Indian Outlet, Rackmount, 230V, India | SRV2KL-IN | Downloaded on 06/03/2019 (EST)



APC Easy UPS Online 2000VA, Indian Outlet, Rackmount, 230V, India

SRV2KL-IN

Call for More Information 18001030011

- High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions
- Includes: Documentation CD, Qty 1- Detachable IEC Power Cord, Rack Mounting brackets, Stabilization / Wall mounting feet, USB cable, User Manual

Output

Output power capacity	1.6kWatts / 2.0kVA
Max Configurable Power (Watts)	1.6kWatts / 2.0kVA
Nominal Output Voltage	230V
Efficiency at Full Load	88.0 %
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Other Output Voltages	220, 240
Topology	Double Conversion Online
Waveform type	Sine wave
Bypass	Built-in Bypass

Input

Nominal Input Voltage	230V
Input frequency	40 - 70 Hz
Input Connections	IEC-320 C14
Cord Length	1.48meters
Number of Power Cords	1
Efficiency at Full Load	88.0 %

Batteries & Runtime

Battery type	VRLA
Included Battery Modules	1
Typical recharge time	4hour(s)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Technical Specifications

APC Easy UPS Online 2000VA, Indian Outlet, Rackmount, 230V, India | SRV2KL-IN | Downloaded on 06/03/2019 (EST)

Communications & Management

Control panel	Multi-function LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity
Emergency Power Off (EPO)	--

Surge Protection and Filtering

Surge energy rating	600Joules
---------------------	-----------

Physical

Maximum Height	88MM, 8.8CM
Maximum Width	438MM, 43.8CM
Maximum Depth	11735MM, 1173.5CM
Rack Height	2U
Net Weight	18.2KG
Shipping weight	21.0KG
Shipping Height	218MM, 21.8CM
Shipping Width	550MM, 55.0CM
Shipping Depth	700MM, 70.0CM
Color	Black

Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 (non-condensing) %
Operating Elevation	0-3000meters
Storage Temperature	-20 - 60 °C
Storage Relative Humidity	0 - 95 (non-condensing) %
Storage Elevation	0-3000meters
Protection Class	IP 20

Conformance

Approvals	BIS
Standard warranty	2 year (manufacturer's defect)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.