

You are here: [Home](#) > [Products](#) > [Uninterruptible Power Supply \(UPS\)](#) > [Smart-UPS On-Line](#)



APC Smart-UPS RC 10000VA 230V for India - No Batteries
Part Number: SRC10KUXI



[Technical Specifications](#) [Product Overview](#) [Documentation](#) [Software & Firmware](#) [Options](#)

Output

Output Power Capacity	9000 Watts / 10 kVA
Max Configurable Power	9000 Watts / 10 kVA
Nominal Output Voltage	220V, 230V, 240V
Efficiency at Full Load	94.0%
Output Voltage Distortion	Less than 2%
Output Frequency (sync to mains)	47 - 53 Hz for 50 Hz nominal, 50/60 Hz +/-1 Hz , 50/60Hz +/- 3 Hz
Waveform Type	Sine wave
Output Connections	(1) Hard Wire 3-wire (H N + G)
Output Voltage THD	< 2% for 0 to 100% linear load and < 5% for full non linear load
Bypass	Built-in Static Bypass

Input

Nominal Input Voltage	230V
Input Frequency	40 - 70 Hz (auto sensing)
Input Connections	Hard Wire 3 wire (1PH+N+G) Hard Wire 5-wire (3PH + N + G)
Input voltage range for main	160 - 285V

operations

Batteries & Runtime

Battery Type	No internal battery - uses external battery system
--------------	--

Communications & Management

Interface Port(s)	RJ-45 Serial, USB
-------------------	-------------------

Emergency Power Off (EPO)	Yes
---------------------------	-----

Physical

Maximum Height	433.00 mm
----------------	-----------

Maximum Width	134.00 mm
---------------	-----------

Maximum Depth	706.00 mm
---------------	-----------

Net Weight	27.50 KG
------------	----------

Shipping Weight	32.00 KG
-----------------	----------

Shipping Height	570.00 mm
-----------------	-----------

Shipping Width	275.00 mm
----------------	-----------

Shipping Depth	790.00 mm
----------------	-----------

Environmental

Operating Environment	0 - 40 °C
-----------------------	-----------

Operating Relative Humidity	0 - 95% no%
-----------------------------	-------------

Operating Elevation	0-3000 meters
---------------------	---------------

Storage Temperature	-10 - 60 °C
---------------------	-------------

Storage Relative Humidity	0 - 95% no%
---------------------------	-------------

Storage Elevation	0-15000 meters
-------------------	----------------

Audible noise at 1 meter from surface of unit	55.00 dBA
---	-----------

Protection Class	IP 20
------------------	-------

Conformance

Standard Warranty	2 years repair or replace
-------------------	---------------------------

Sustainable Offer Status

RoHS	Compliant
------	-----------

REACH	REACH: Contains No SVHCs
-------	--------------------------