

## Solutions

## Products and Services

## Support

## Your Business

## Company

Share:



## APC Smart-UPS RC 1000VA 230V India Harsh Environment SRC1KUXI



APC Smart-UPS RC 1000VA 230V India Harsh Environment

Call for More Information  
18001030011

Includes: Smart UPS signalling RS-232 cable , USB cable , User Manual , Warranty card

Locate a Partner

### Related Products, Accessories & Services

[View all optional accessories for this product](#)



Dry Contact I/O SmartSlot Card

Call for More Information  
18001030011



Out-Of-Band Management SmartSlot Card

Call for More Information  
18001030011



UPS Network Management Card 2

Call for More Information  
18001030011

## Product Overview

## Technical Specifications

## Documentation

## Software &amp; Firmware

## Options

#### Output

Output power capacity	800 Watts / 1.0 kVA
Max Configurable Power (Watts)	800 Watts / 1.0 kVA
Nominal Output Voltage	230V
Efficiency at Full Load	90.0 %
Output Voltage Distortion	Less than 2%
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Other Output Voltages	220, 240
Load Crest Factor	3 : 1
Topology	Delta Conversion On-Line
Waveform type	Sine wave
Output Connections	(4) India 3-pin 6A (Battery Backup)

#### Input

Nominal Input Voltage	230V
Input frequency	40 - 70 Hz

Input Connections	India 3-pin 6A
Cord Length	1.52 meters
Input voltage range for main operations	100 - 280 (half load) V
Number of Power Cords	1
Efficiency at Full Load	90.0 %

## Batteries & Runtime

Battery type	No internal battery - uses external battery system
--------------	--

## Communications & Management

Interface Port(s)	DB-9 RS-232 , Smart-Slot
Control panel	LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : and Overload Indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Physical

Maximum Height	220 , 22.0 cm
Maximum Width	145 , 14.5 cm
Maximum Depth	400 , 40.0 cm
Net Weight	5.7 kg
Shipping weight	6.3 kg
Shipping Height	340 , 34.0 cm
Shipping Width	235 , 23.5 cm
Shipping Depth	478 , 47.8 cm
Color	Black
Pallet Weight	877.44 lbs.
Units per Pallet	60.0

## Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-900 meters
Storage Temperature	-20 - 60 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-4500 meters

## Conformance

Standard warranty	2 years repair or replace
-------------------	---------------------------