

Share:



## SRC1KI-IN

Description: High density, double-conversion on-line power protection with scalable runtime  
Includes : Smart UPS signalling RS-232 cable , USB cable , User Manual , Warranty card



## Product Support

- User Manual
- Replacement Battery
- Software & Firmware
- Product Registration
- Product FAQs

Product Overview

Technical Specifications

Documentation

Software & Firmware

Options

## Output

Print Technical Specification

Output power capacity	800Watts / 1.0 kVA
Max Configurable Power (Watts)	800Watts / 1.0 kVA
Nominal Output Voltage	230V
Efficiency at Full Load	90.0 %
Output Voltage Distortion	Less than 2%
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Other Output Voltages	220, 240
Load Crest Factor	3 : 1
Topology	Double Conversion Online
Waveform type	Sine wave
Bypass	Built-in Bypass

## Input

Nominal Input Voltage	230V
Input frequency	40 - 70 Hz
Input Connections	India 3-pin 6A
Cord Length	1.52meters
Input voltage range for main operations	110 - 280 (half load)V
Number of Power Cords	1
Efficiency at Full Load	90.0 %

## Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	6hour(s)
Runtime	<a href="#">View Runtime Graph</a> <a href="#">View Runtime Chart</a>

### Communications & Management

---

Interface Port(s)	DB-9 RS-232 , Smart-Slot
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

### Physical

---

Maximum Height	220mm , 22.0CM
Maximum Width	145mm , 14.5CM
Maximum Depth	400mm , 40.0CM
Net Weight	13.5KG
Shipping weight	14.5KG
Shipping Height	340mm , 34.0CM
Shipping Width	235mm , 23.5CM
Shipping Depth	478mm , 47.8CM
Color	Black
Pallet Weight	1686.54lbs.
Units per Pallet	50.0

### Environmental

---

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-900meters
Storage Temperature	-20 - 60 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-4500meters

### Conformance

---

Standard warranty	2 years repair or replace
-------------------	---------------------------