



Share:

APC Smart-UPS RC 6000VA 230V for India - No Batteries

SRCE6KUXI

APC Smart-UPS RC 6000VA 230V for India - No Batteries

Includes: Smart UPS signalling RS-232 cable , User Manual

Call for More Information  
18001030011

Locate a Partner

Related Products, Accessories & Services

View all optional accessories for this product

5 X 8 Power Up For (1) Smart-UPS 5-7kVA

Call for More Information  
18001030011

1 Year NBD 1P Advantage Plan For Smart-UPS 5K-7K

Call for More Information  
18001030011

1 Year Renewal Extended Warranty For (1) Smart-UPS 5-7kVA

Call for More Information  
18001030011

Product Overview

Technical Specifications

Documentation

Options

Output

Output power capacity	5.4 KWatts / 6.0 kVA
Max Configurable Power (Watts)	5.4 KWatts / 6.0 kVA
Nominal Output Voltage	230V
Output Voltage Note	Configurable for 220 : 230 or 240 nominal output voltage
Output Voltage Distortion	Less than 5%
Other Output Voltages	220, 240
Topology	Double Conversion Online
Waveform type	Sine wave
Output Connections	(1) Hard Wire 3-wire (H N + G) (Battery Backup)
Bypass	Built-in Static Bypass

Input

Nominal Input Voltage	230V
Input frequency	40 - 70 Hz
Input Connections	Hard Wire 3-wire
Input voltage range for main operations	160 - 285 V

Batteries & Runtime

Battery type	No internal battery - uses external battery system
Efficiency	<a href="#">View Efficiency Graph</a>

Communications & Management

Control panel	Multi-function LCD status and control console
Audible Alarm	Audible and visible alarms : configurable delays
Emergency Power Off (EPO)	Yes
Available SmartSlot™ Interface Quantity	1

Surge Protection and Filtering

Surge energy rating	480 Joules
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum Height	476 mm , 47.6 cm
Maximum Width	135 mm , 13.5 cm
Maximum Depth	706 mm , 70.6 cm
Net Weight	18.71 kg
Shipping weight	23.45 kg
Shipping Height	570 mm , 57.0 cm
Shipping Width	275 mm , 27.5 cm
Shipping Depth	790 mm , 79.0 cm

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-900 meters
Storage Temperature	-15 - 65 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-3000 meters
Audible noise at 1 meter from surface of unit	55.0 dBA

Conformance

Standard warranty	2 years repair or replace
-------------------	---------------------------



Sign up to stay up to date with best practices, new solutions and special offers.

Email

OK

WHO WE ARE  
CONNECT WITH US  
FIND A RESELLER  
Zip/Postal Code  
CATALOG KEYCODE  
Enter Key Code

FIND  
GO



[TERMS & CONDITIONS](#) >

[PRIVACY STATEMENT](#) >

© 2015, APC by Schneider Electric