

## Technical Specifications

APC Smart-UPS 1500VA USB & Serial 230V, India Specific | SUA1500I-IND | Downloaded on 10/13/2020 (EST)



## APC Smart-UPS 1500VA USB & Serial 230V, India Specific

SUA1500I-IND

Call for More Information 18001030011

- Includes: Smart UPS signalling RS-232 cable, USB cable, User manual

### Output

Output power capacity	980 Watts / 1.5kVA
Max Configurable Power (Watts)	980 Watts / 1.5kVA
Nominal Output Voltage	230V
Output Voltage Note	Configurable for 220 : 230 or 240 nominal output voltage
Output Voltage Distortion	Less than 5 %
Output Frequency (sync to mains)	47 - 53 Hz For 50 Hz nominal Sync to mains
Topology	Line interactive
Waveform type	Sine wave
Output Connections	(4) India 3-pin 6A

### Input

Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 3 Hz Auto-sensing
Input Connections	IEC 60320 C14
Input voltage range for main operations	151 - 302 Adjustable, 160 - 286V

### Batteries & Runtime

Battery type	Lead-acid battery
Typical recharge time	3hour(s)
Expected Battery Life (years)	2 - 4
Battery Charge Power (Watts)	136 Watts
Battery Volt-Amp-Hour Capacity	408

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

APC Smart-UPS 1500VA USB & Serial 230V, India Specific | SUA1500I-IND | Downloaded on 10/13/2020 (EST)

### Batteries & Runtime

Runtime	View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site)
---------	--

### Communications & Management

Interface Port(s)	DB-9 RS-232, SmartSlot, USB
Control panel	LED status display with on line : on battery : replace battery and overload indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

### Surge Protection and Filtering

Surge energy rating	480Joules
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

### Physical

Maximum Height	216MM, 21.6CM
Maximum Width	170MM, 17.0CM
Maximum Depth	439MM, 43.9CM
Net Weight	24.04KG
Shipping weight	26.76KG
Shipping Height	370MM, 37.0CM
Shipping Width	330MM, 33.0CM
Shipping Depth	590MM, 59.0CM
Units per Pallet	24.0

### Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-15 - 45 °C
Storage Elevation	0 - 15240meters
Audible noise at 1 meter from surface of unit	45.0dBA
Online thermal dissipation	135.0BTU/hr

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

# Technical Specifications

APC Smart-UPS 1500VA USB & Serial 230V, India Specific | SUA1500I-IND | Downloaded on 10/13/2020 (EST)



Conformance	
Approvals	BIS
Standard warranty	2 years repair or replace

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.